

HAND HELD COMPUTER

2410 Series

Benefits:

- **Small, lightweight design**
- **Newest IEEE 802.11 wireless standards**
- **Industry standard development and connectivity tools**
- **Upgradeable wireless and batch versions provide investment protection**
- **Long lasting Lithium Ion battery for full shift operation**
- **Survives 4-foot drops to concrete**

With its compact, lightweight packaging, the 2410 Series hand-held computers are designed for retail and light industrial environments. Weighing under 14 oz., the 2410 Series provides easy operation over extended periods.

As the newest addition to the Intermec 2400 product line, 2410 Series hand-held computers share applications with other members of 2400 family. You can run the same application on a stationary shop floor terminal, a 2410 Series hand-held computer, and a vehicle mount unit.

With its industry-standard internal PC card slot, the 2410 Series can adapt with your system as your data collection needs change. You can start with the 2410—a hardwired (batch) system—and upgrade to the 2415—an 802.11 standard wireless system—simply by sending it to an Intermec service center for an RF upgrade. The 2415 can also be upgraded with the latest technology so you can easily change radios to handle higher speeds and increased coverage as advances in standards such as 802.11 RF technology occur.

You can also count on the 2410 Series to put in a full day's work without recharging. Its state-of-the-art Lithium Ion battery is easy to recharge and can run 8 to 10 hours on a single charge. That



makes the 2410 ideal for time-intensive applications, such as in-store audits and re-stocking inventory. And its high-contrast, scratch resistant display makes for easy reading in many environments. Best of all, 2410 Series hand held computers integrate seamlessly into your system, whether it is terminal emulation, client/server or simple serial connection through a communications dock.

2410 Series

Physical characteristics

Length: 19.3 cm (7.6")

Width: 8.4 cm (3.3") at scanner; 5 cm (2") at grip

Height: 5.6 cm (2.2") at scanner; 3 cm (1.2") at grip

Weight (with standard battery):

Model 2410 (Batch): 374g (13.2 oz.)

Model 2415 (RF): 422g (14.9 oz.)

Add 43g (1.5 oz.) for high capacity battery

Display

CGA compatible backlit LCD displaying 16 lines of 20 characters per line (160 x 128 dot matrix) plus LED status indicators

Full 25 x 80 virtual screen with viewporting

U.S. and European character sets plus Big 5 and Simplified Chinese, Korean, and Japanese

Keyboard

Elastomeric 55-key with full alphanumeric set or 37-key with larger numeric.

Options for U.S., Multilingual European, IBM 3270/5250, and VT/ANSI

Environmental

Operating temperature: -20° to 50°C (-4° to 122°F)

Storage temperature: -20° to 60°C (-4° to 140°F)

Humidity: Non-condensing (0 to 95% RH)

Bar Code Scanning Options

Integrated visible laser diode scanner

USA/Canada Class II. International Class 2

Depth of Field—Standard Range* (670nm) (measured for Code 39)

5 mil	9.4-15.7 cm	(3.7"-6.2")
10 mil	7.4-30.5 cm	(2.9"-12")
20 mil	10.2-63.5 cm	(4"-25")
30.0 mil	10.2-86.4 cm	(4"-34")
40.0 mil	12.7-99 cm	(5"-39")
55.0 mil	19.1-126 cm	(7.5"-49")
55 mil retroreflective	105-151 cm	(41"-59")
100 mil retroreflective	113-227 cm	(44"-89")

Depth of Field—Long Range* (650nm)

10 mil	29.4-49.8 cm	(11.6-19.6")
20 mil	21.8-98 cm	(8.6 - 38.6")
30 mil	24.4-192 cm	(9.6 - 75.6")
40 mil	24.4-204.7 cm	(9.6-80.6")
70 mil retroreflective	192-410.5 cm	(75.6-162")
100 mil retroreflective	212.3-532.4 cm	(83.6"-209.6")

Built-in 16 pin I/O connector for attaching Intermec decoded and undecoded scanners and wands. Adapter available.

Measured for Code 39

Bar Codes Supported

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN Code 128, Code 11, Code 93, Plessey, MSI, Code 16K, Code 49

Power

Operating: Lithium Ion battery pack, standard and high capacity

Memory

RAM: 1 MB, battery backed

Non-volatile Memory: 2MB Standard, 4MB optional

Additional Storage: 2 or 4MB SRAM (batch only)

Integrated RF Module Options

Frequency: 2.4 GHz frequency band, actual frequencies in use varies by country

WLI forum OpenAir:

Type: Frequency Hopping Spread Spectrum (FHSS)

Power Outputs: 100mW

Data Rate: 1.6 Mbps, .8 Mbps fallback

Range*: 1500+ ft. (450+ m) outdoors

IEEE 802.11b High Rate (11 Mbps):

Type: Direct Sequence Spread Spectrum

Data Rates: 11/5.5/2/1 Mbps with Auto fallback for increased range

Range* at 1 Mbps: 1750ft. (533m) outdoors, 165ft. (50m) indoors

Range* at 11 Mbps: 525ft. (160m) outdoors, 80ft. (24m) indoors

Security: Wired Equivalent Privacy (WEP)

*Unlimited with roaming

Serial Data Communications

Built-in serial connector, 9-pin adapter optional

RS232-C up to 38.4 Kbps

XMODEM, YMODEM for data transfer

Supports configurable Serial Protocol and XON/OFF

Host Support via Data Collection Server 300

Host Environment: IBM AS 400, Digital HP, UNIX, Windows NT

Connectivity: Ethernet, Token Ring, 100BASE-T, Twinax, Coax, SDLC

Communications: TCP/IP, SNA

Direct TCP/IP Support

Sockets interface or terminal emulation Ethernet or Token Ring

Software Configurations

Programmable: Microsoft® CC++, DOS

Terminal Emulation: 3270/5250 SNA and TELNET and ANSI/VT 100, 220, 320

Web-enabled HTML support with dc Browser™

Shock and Vibration Protection

Warranted for 4-foot drop to concrete

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TÜV Rheinland GS, EN 60950 and EN 60825-1, FCC Part 15, Canada, RSS210 and ICES-003, Class B, EN 55022/CISPR 22, Class B, ETS 300 328, ETS 300 826, Compliant with all European directives, CE marked.

Accessories

Battery charger, battery pack available in standard and high capacity, pistol grip handle, holster, belt loop, hand strap, serial communications dock, User manual, Programmer's Software Kit (PSK), EZBuilder™ Rapid Application Development software.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

Internet • www.intermec.com **Sales** • 800.347.2636 (toll free in N.A.), 425.348.2726 **Service and Support** • 800.755.5505 (toll free in N.A.), 425.356.1799

North America
Corporate Headquarters • 6001 36th Avenue West, Everett, Washington 98203, tel: 425.348.2600, fax: 425.355.9551
Systems & Solutions • 550 2nd Street S.E., Cedar Rapids, Iowa 52401, tel: 319.369.3100, fax: 319.369.3453
Media Supplies • 9290 Le Saint Drive, Fairfield, Ohio 45014, tel: 513.874.5882, fax: 513.874.8487

Europe/Middle East & Africa
Headquarters • Sovereign House, Vastern Road, Reading, Berkshire RG1 8BT, United Kingdom, tel: +44.118.987.9400, fax: +44.118.987.9401
Gothenburg • Idrottsvägen 10, P.O. Box 123, SE-431 22 Mölndal, Sweden, tel: +46.31.869500, fax: +46.31.869595

Asian Pacific/Latin America
Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, Hong Kong, tel: 852.2574.9777, fax: 852.2574.9725
Singapore • 25-16 International Plaza, 10 Anson Road, 079903, tel: 65.324.8391, fax: 65.324.8393
Australia • 15 Stamford Road, Oakleigh, Victoria 3166, tel: 61.3.9563.0000, fax: 61.3.9563.4000
South America and Mexico • 2572 White Road, Irvine, California 92614, tel: 949.975.1905, fax: 949.975.1913

Worldwide Fax Document Retrieval Service • 800.755.5505 (North America Only) • tel: 650.556.8447

Copyright © 2000 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608762-01C 12/00

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.